

SAND TEX

The sole anti scratch printable tex high
tack removable for floor graphic

SOLVENT (SETX2LT)

Floor appeal LT

Sand Tex LT is 100% Pet Fabric adhesive for smooth floor surface.

1. 100% fabric

- Soft and easy
- Texture surface
- Stable printing with Latex heat
- Ink dry fast
- Perfect sharpness of image
- Tiled together edge
- No shrink
- No tear
- No residue
- Eco friendly

2. Perfect anti-scratch and anti-slip

- The special bead technology provide wonderful wear resistance and nonskid fuction

3. Best sharpness of printing quality

- It is the best sharpness of printed image

SPECIFICATION

Base Material 100% polyester fabric
Surface Bead matte

Base Caliper (Include adh) 360 μ m \pm 50
Liner Caliper (Paper) 150 μ m \pm 20
Total Caliper 510 μ m \pm 55

Base Weight (GSM) 240gsm \pm 50
Liner Weight (GSM) 150gsm \pm 30
Total Weight (GSM) 390gsm \pm 50

Width 60", 54", 30"
Length 30m (100ft), 15m (50ft)
Core 3"

COMPATIBILITY

INK compatibility
Solvent, Eco-solvent, Mild-solvent, Latex, UV

Printer compatibility
Most solvent, Latex, and UV printing system

APPLICATION

- * Smooth floor surface
- * Retail shop event, temporary event, sponsorship targeted marketing, promotional events, way-finding, path to purchase, facility safety

NOTE

Printing condition 15~30°C (59~86°F) / Humidity 30~60%
Storage Stored at 10~25°C (50~77°F)
Humidity 50~55% RH
Shelf Life 1 year stored in original package
under above condition

The above descriptions are tested by our own efforts based on international standard.

All descriptions can be changed as the case may be without any prior notification. No media warranty is implied.

This specification sheet shall be used only within the purpose of its defined usage and also shall not be copied without the Sipos approval.



SIPOS compnay

Doosan the landpark A807, Magokungang-ro 161-8, Gangseo-gu, South Korea

TEL +82 (0)70 7807 1206 Fax: +82 (0)70 7610 9221

sipos.kr